

E HSS jobber drills with split point AC, DIN 338 RN

Range of application:

Industrial quality twist drill for drilling steel and steel castings, alloyed carbon and plain steel, grey iron castings, copper-alloys, nickel-silver, graphite and similar materials.




Industrial quality



Highly accurate centering



Precise



HSS

Typ/Type/Tipo
RNKreuzanschliff
Split Point
AC
 Oberfläche: dampfangelassen
 Surface: steam tempered
 Superficie: templado al vapor
DIN
338

Industrial packing

d1 mm	l1 mm	l2 mm	Code 601 Art.-Nr.	Cont.
0,20	19	25	0060100020100	10
0,30	19	3	0060100030100	10
0,35	20	5	0060100035100	10
0,40	20	5	0060100040100	10
0,50	22	6	0060100050100	10
0,55	24	7	0060100055100	10
0,60	24	7	0060100060100	10
0,65	26	8	0060100065100	10
0,70	29	9	0060100070100	10
0,75	28	9	0060100075100	10
0,80	30	10	0060100080100	10
0,85	30	10	0060100085100	10
0,90	32	11	0060100090100	10
0,95	32	11	0060100095100	10
1,00	34	12	0060100100100	10
1,05	34	12	0060100105100	10
1,10	36	14	0060100110100	10
1,15	36	14	0060100115100	10
1,20	38	16	0060100120100	10
1,25	38	16	0060100125100	10
1,30	38	16	0060100130100	10
1,35	40	18	0060100135100	10



Metal drills and stainless steel drills