

E HSS Cobalt jobber drills, DIN 338 RN

Range of application:

5% cobalt-alloyed jobber drills with high heat-resistance for drilling steels with tensile strength over 800 N/mm², specially suitable for high alloyed steels, bearing-steels, hot/cold-rolled steel. Ideal for stainless steel.




Highly accurate centering



Break-resistant



Industrial quality



Single pack



Industrial packing



Metal drills and stainless steel drills

				bright			bright		
d1 mm	d1 inch	l1 mm	l2 mm	Code 623 Art.-Nr.	Cont.		Code 613 Art.-Nr.	Cont.	
1,00		34	12	0062300100100	1	10	0061300100100	10	
1,10		36	14				0061300110100	10	
1,19	3/64	38	16				0061300119100	10	
1,20		38	16				0061300120100	10	
1,30		38	16				0061300130100	10	
1,40		40	18				0061300140100	10	
1,50		40	18	0062300150100	1	10	0061300150100	10	
1,59	1/16	43	20				0061300159100	10	
1,60		43	20				0061300160100	10	
1,70		43	20				0061300170100	10	
1,80		46	22				0061300180100	10	
1,90		46	22				0061300190100	10	
1,98	5/64	49	24				0061300198100	10	
2,00		49	24	0062300200100	1	10	0061300200100	10	
2,10		49	24				0061300210100	10	
2,20		53	27				0061300220100	10	
2,30		53	27				0061300230100	10	
2,38	3/32	57	30				0061300238100	10	
2,40		57	30				0061300240100	10	
2,50		57	30	0062300250100	1	10	0061300250100	10	
2,60		57	30				0061300260100	10	
2,70		61	33				0061300270100	10	