

E HSS jobber drills, short DIN 338 RN

Range of application:

HSS twist drill: toughness and precision combined with excellent cutting efficiency for drilling alloyed carbon and plain steel. Ideal for hand held operations.



Resilient



Fast drilling progress



Long tool life



Single pack



Industrial packing



Industrial packing with tag

d1 mm	d1 inch	l1 mm	l2 mm	Code 618 Art.-Nr.	Cont.	Code 626 Art.-Nr.	Cont.	Code 631 Art.-Nr.	Cont.
0,40	1/64	20	5			0062600040100	10		
0,79	1/32	30	10			0062600079100	10		
1,00		34	12	0061800100100	3 10	0062600100100	10	0063100100100	10
1,10		36	14			0062600110100	10		
1,19	3/64	38	16			0062600119100	10		
1,20		38	16			0062600120100	10		
1,25		38	16			0062600125100	10		
1,30		38	16			0062600130100	10		
1,40		40	18			0062600140100	10		
1,50		40	18	0061800150100	3 10	0062600150100	10	0063100150100	10
1,59	1/16	43	20			0062600159100	10		
1,60		43	20			0062600160100	10		
1,70		43	20			0062600170100	10		
1,75		46	22			0062600175100	10		
1,80		46	22			0062600180100	10		
1,90		49	24			0062600190100	10		
1,98	5/64	49	24			0062600198100	10		
2,00		49	24	0061800200100	3 10	0062600200100	10	0063100200100	10
2,10		49	24			0062600210100	10		
2,20		53	27			0062600220100	10		
2,25		53	27			0062600225100	10		