

E HSS jobber drills, short DIN 338 RN

Range of application:

HSS twist drill: toughness and precision combined with excellent cutting efficiency for drilling alloyed carbon and plain steel. Ideal for hand held operations.




Resilient



Fast drilling progress



Long tool life



Oberfläche: Sonderbehandlung
Surface: Special treatment
Superficie: Tratamiento especial



Single pack



Industrial packing



Industrial packing with tag

d1 mm	d1 inch	l1 mm	l2 mm	Code 618 Art.-Nr.	Cont.	Code 626 Art.-Nr.	Cont.	Code 631 Art.-Nr.	Cont.
0,40	1/64	20	5			0062600040100	10		
0,79	1/32	30	10			0062600079100	10		
1,00		34	12	0061800100100	3 10	0062600100100	10	0063100100100	10
1,10		36	14			0062600110100	10		
1,19	3/64	38	16			0062600119100	10		
1,20		38	16			0062600120100	10		
1,25		38	16			0062600125100	10		
1,30		38	16			0062600130100	10		
1,40		40	18			0062600140100	10		
1,50		40	18	0061800150100	3 10	0062600150100	10	0063100150100	10
1,59	1/16	43	20			0062600159100	10		
1,60		43	20			0062600160100	10		
1,70		43	20			0062600170100	10		
1,75		46	22			0062600175100	10		
1,80		46	22			0062600180100	10		
1,90		49	24			0062600190100	10		
1,98	5/64	49	24			0062600198100	10		
2,00		49	24	0061800200100	3 10	0062600200100	10	0063100200100	10
2,10		49	24			0062600210100	10		
2,20		53	27			0062600220100	10		
2,25		53	27			0062600225100	10		