Quick Dry

# Rustins

# Small Job Gloss Paint

## GLOSS

**Black**

toy safe

low odour

Made in UK

**For indoor & outdoor use**

**SMALL JOB GLOSS PAINT RANGE**

| | |
|---|---|
| CHOCOLATE | DELPHINIUM |
| BUTTERCUP | MAGNOLIA |
| OXFORD BLUE | CANDY PINK |
| POPPY | BLACK |
| BUCKINGHAM GREEN | WHITE |

IMPORTANT: THESE COLOURS ARE AS CLOSE TO THE ACTUAL COLOUR AS THE PRINTING PROCESS PERMITS

**STIR WELL BEFORE USE**

**A water based hardwearing paint for interior & exterior use that is touch dry in approximately 30 minutes. Suitable for use on wood and metal. Conforms to the Toys (Safety) Regulations 1995, BS:EN71 Part 3.**

## Preparation

The surface must be clean and free from wax and grease. If already painted, remove flaking paint by scraping or with Rustins Strypit Paint and Varnish Stripper. If applying to metal, remove any rust with a scraper or with Rustins Rust Remover and apply one coat of Quick Dry Rustins Red Oxide Metal Primer. It is not necessary to apply Knotting to knots on bare wood, but if the wood is very absorbent, a coat of Rustins Primer & Undercoat may be applied before applying the paint.

## Application

STIR WELL BEFORE USE: Apply liberally and evenly with a synthetic fibre brush. Do not use below 10ºC, in damp conditions or if rain is imminent.

## Re-coating Time

The paint will be touch dry in approximately 30 minutes depending on temperature and humidity and can be re-coated after 2 hours.

## Coverage

1 litre will cover approximately 12 sq.m in 1 coat depending on the absorbency of the surface.

## Cleaning

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

## Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

## Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

**HEALTH AND SAFETY**

Contains 5-chloro-2-methyl-2h-isothiazol-3-one (acticide fsn). May produce an allergic reaction.

Keep out of reach of children.

Do not get in eyes, on skin, or on clothing.

IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.

Wear protective gloves and eye protection.

IF ON SKIN: Gently wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

For information on Rustins' products visit our website at **www.rustins.co.uk** or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom
**rustins@rustins.co.uk**
Telephone: +44 (0)20 8450 4666

LOW VOC CONTENT 0.30% to 7.99%
*VOCs. (Volatile Organic Compounds) contribute to atmospheric pollution.*
PROTECTED. USED UNDER LICENCE.

EU limit value for this product (cat A/i): 130g/l (2010).
This product contains max 74g/l VOC.

5 015332 001798

**500ml** e

Quick Dry

# Rustins Small Job Gloss Paint

## GLOSS

Chocolate

toy safe

low odour

Made in UK

**For indoor & outdoor use**

**SMALL JOB GLOSS PAINT RANGE**

| | |
|---|---|
| CHOCOLATE | DELPHINIUM |
| BUTTERCUP | MAGNOLIA |
| OXFORD BLUE | CANDY PINK |
| POPPY | BLACK |
| BUCKINGHAM GREEN | WHITE |

IMPORTANT: THESE COLOURS ARE AS CLOSE TO THE ACTUAL COLOUR AS THE PRINTING PROCESS PERMITS

**STIR WELL BEFORE USE**

**A water based hardwearing paint for interior & exterior use that is touch dry in approximately 30 minutes. Suitable for use on wood and metal. Conforms to the Toys (Safety) Regulations 1995, BS:EN71 Part 3.**

## Preparation

The surface must be clean and free from wax and grease. If already painted, remove flaking paint by scraping or with Rustins Strypit Paint and Varnish Stripper. If applying to metal, remove any rust with a scraper or with Rustins Rust Remover and apply one coat of Quick Dry Rustins Red Oxide Metal Primer. It is not necessary to apply Knotting to knots on bare wood, but if the wood is very absorbent, a coat of Rustins Primer & Undercoat may be applied before applying the paint.

## Application

STIR WELL BEFORE USE: Apply liberally and evenly with a synthetic fibre brush. Do not use below 10ºC, in damp conditions or if rain is imminent.

## Re-coating Time

The paint will be touch dry in approximately 30 minutes depending on temperature and humidity and can be re-coated after 2 hours.

## Coverage

1 litre will cover approximately 12 sq.m in 1 coat depending on the absorbency of the surface.

## Cleaning

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

## Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

## Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

**HEALTH AND SAFETY**

Contains 5-chloro-2-methyl-2h-isothiazol-3-one (acticide fsn). May produce an allergic reaction.

Keep out of reach of children.

Do not get in eyes, on skin, or on clothing.

IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.

Wear protective gloves and eye protection.

IF ON SKIN: Gently wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

For information on Rustins' products visit our website at **www.rustins.co.uk** or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom
**rustins@rustins.co.uk**
Telephone: +44 (0)20 8450 4666

LOW VOC CONTENT 0.30% to 7.99%
VOCs. (Volatile Organic Compounds) contribute to atmospheric pollution.
PROTECTED, USED UNDER LICENCE

EU limit value for this product (cat A/i): 130g/l (2010).
This product contains max 74g/l VOC.

5 015332 001828

**500ml** e

Rustins

Quick Dry

# Small Job Gloss Paint

## GLOSS

**White**

toy safe

low odour

Made in UK

**For indoor & outdoor use**

**SMALL JOB GLOSS PAINT RANGE**

| | |
|---|---|
| CHOCOLATE | DELPHINIUM |
| BUTTERCUP | MAGNOLIA |
| OXFORD BLUE | CANDY PINK |
| POPPY | BLACK |
| BUCKINGHAM GREEN | WHITE |

IMPORTANT: THESE COLOURS ARE AS CLOSE TO THE ACTUAL COLOUR AS THE PRINTING PROCESS PERMITS

**STIR WELL BEFORE USE**

**A water based hardwearing paint for interior & exterior use that is touch dry in approximately 30 minutes. Suitable for use on wood and metal. Conforms to the Toys (Safety) Regulations 1995, BS:EN71 Part 3.**

## Preparation

The surface must be clean and free from wax and grease. If already painted, remove flaking paint by scraping or with Rustins Strypit Paint and Varnish Stripper. If applying to metal, remove any rust with a scraper or with Rustins Rust Remover and apply one coat of Quick Dry Rustins Red Oxide Metal Primer. It is not necessary to apply Knotting to knots on bare wood, but if the wood is very absorbent, a coat of Rustins Primer & Undercoat may be applied before applying the paint.

## Application

STIR WELL BEFORE USE: Apply liberally and evenly with a synthetic fibre brush. Do not use below 10ºC, in damp conditions or if rain is imminent.

## Re-coating Time

The paint will be touch dry in approximately 30 minutes depending on temperature and humidity and can be re-coated after 2 hours.

## Coverage

1 litre will cover approximately 12 sq.m in 1 coat depending on the absorbency of the surface.

## Cleaning

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

## Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

## Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

**HEALTH AND SAFETY**

Contains 5-chloro-2-methyl-2h-isothiazol-3-one (acticide fsn). May produce an allergic reaction.

Keep out of reach of children.

Do not get in eyes, on skin, or on clothing.

IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.

Wear protective gloves and eye protection.

IF ON SKIN: Gently wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

For information on Rustins' products visit our website at **www.rustins.co.uk** or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom
**rustins@rustins.co.uk**
Telephone: +44 (0)20 8450 4666

LOW VOC CONTENT 0.30% to 7.99%
VOCs. (Volatile Organic Compounds) contribute to atmospheric pollution.
PROTECTED, USED UNDER LICENCE

EU limit value for this product (cat A/i): 130g/l (2010).
This product contains max 74g/l VOC.

5 015332 001903

**500ml** e

20160310_LAB_0220800_QD Small Job 500ml_0214049 Small Job 500ml 14/03/2016 15:29 Page 4

Quick Dry

# Rustins Small Job Gloss Paint

## GLOSS

**Poppy**

toy safe

low odour

Made in UK

**For indoor & outdoor use**

**SMALL JOB GLOSS PAINT RANGE**

| | |
|---|---|
| CHOCOLATE | DELPHINIUM |
| BUTTERCUP | MAGNOLIA |
| OXFORD BLUE | CANDY PINK |
| POPPY | BLACK |
| BUCKINGHAM GREEN | WHITE |

IMPORTANT: THESE COLOURS ARE AS CLOSE TO THE ACTUAL COLOUR AS THE PRINTING PROCESS PERMITS

**STIR WELL BEFORE USE**

**A water based hardwearing paint for interior & exterior use that is touch dry in approximately 30 minutes. Suitable for use on wood and metal. Conforms to the Toys (Safety) Regulations 1995, BS:EN71 Part 3.**

## Preparation

The surface must be clean and free from wax and grease. If already painted, remove flaking paint by scraping or with Rustins Strypit Paint and Varnish Stripper. If applying to metal, remove any rust with a scraper or with Rustins Rust Remover and apply one coat of Quick Dry Rustins Red Oxide Metal Primer. It is not necessary to apply Knotting to knots on bare wood, but if the wood is very absorbent, a coat of Rustins Primer & Undercoat may be applied before applying the paint.

## Application

STIR WELL BEFORE USE: Apply liberally and evenly with a synthetic fibre brush. Do not use below 10ºC, in damp conditions or if rain is imminent.

## Re-coating Time

The paint will be touch dry in approximately 30 minutes depending on temperature and humidity and can be re-coated after 2 hours.

## Coverage

1 litre will cover approximately 12 sq.m in 1 coat depending on the absorbency of the surface.

## Cleaning

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

## Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

## Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

**HEALTH AND SAFETY**

Contains 5-chloro-2-methyl-2h-isothiazol-3-one (acticide fsn). May produce an allergic reaction.

Keep out of reach of children.

Do not get in eyes, on skin, or on clothing.

IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.

Wear protective gloves and eye protection.

IF ON SKIN: Gently wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

For information on Rustins' products visit our website at **www.rustins.co.uk** or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom
**rustins@rustins.co.uk**
Telephone: +44 (0)20 8450 4666

LOW VOC CONTENT 0.30% to 7.99%
VOCs. (Volatile Organic Compounds) contribute to atmospheric pollution.
PROTECTED, USED UNDER LICENCE

EU limit value for this product (cat A/i): 130g/l (2010).
This product contains max 74g/l VOC.

5 015332 001880

**500ml** e

20160310_LAB_0220800_QD Small Job 500ml_0214049 Small Job 500ml 14/03/2016 15:29 Page 5

Quick Dry

# Rustins Small Job Gloss Paint

## GLOSS

## Oxford Blue

toy safe

low odour

Made in UK

**For indoor & outdoor use**

**SMALL JOB GLOSS PAINT RANGE**

| | |
|---|---|
| CHOCOLATE | DELPHINIUM |
| BUTTERCUP | MAGNOLIA |
| OXFORD BLUE | CANDY PINK |
| POPPY | BLACK |
| BUCKINGHAM GREEN | WHITE |

IMPORTANT: THESE COLOURS ARE AS CLOSE TO THE ACTUAL COLOUR AS THE PRINTING PROCESS PERMITS

**STIR WELL BEFORE USE**

**A water based hardwearing paint for interior & exterior use that is touch dry in approximately 30 minutes. Suitable for use on wood and metal. Conforms to the Toys (Safety) Regulations 1995, BS:EN71 Part 3.**

### Preparation

The surface must be clean and free from wax and grease. If already painted, remove flaking paint by scraping or with Rustins Strypit Paint and Varnish Stripper. If applying to metal, remove any rust with a scraper or with Rustins Rust Remover and apply one coat of Quick Dry Rustins Red Oxide Metal Primer. It is not necessary to apply Knotting to knots on bare wood, but if the wood is very absorbent, a coat of Rustins Primer & Undercoat may be applied before applying the paint.

### Application

STIR WELL BEFORE USE: Apply liberally and evenly with a synthetic fibre brush. Do not use below 10ºC, in damp conditions or if rain is imminent.

### Re-coating Time

The paint will be touch dry in approximately 30 minutes depending on temperature and humidity and can be re-coated after 2 hours.

### Coverage

1 litre will cover approximately 12 sq.m in 1 coat depending on the absorbency of the surface.

### Cleaning

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

### Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

### Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

**HEALTH AND SAFETY**

Contains 5-chloro-2-methyl-2h-isothiazol-3-one (acticide fsn). May produce an allergic reaction.

Keep out of reach of children.

Do not get in eyes, on skin, or on clothing.

IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.

Wear protective gloves and eye protection.

IF ON SKIN: Gently wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

For information on Rustins' products visit our website at **www.rustins.co.uk** or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom
**rustins@rustins.co.uk**
Telephone: +44 (0)20 8450 4666

LOW VOC CONTENT 0.30% to 7.99%
VOCs. (Volatile Organic Compounds) contribute to atmospheric pollution.
PROTECTED, USED UNDER LICENCE

EU limit value for this product (cat A/i): 130g/l (2010).
This product contains max 74g/l VOC.

5 015332 001910

**500ml** e