

## **Expert finishes for wood and metal**

Rustins Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.rustins.co.uk

## October 2018

## PRODUCT DATA SHEET

| October 2018       | PRODUCT DATA SHEET  |
|--------------------|---|
| Product            | Quick Dry Textured Step & Tile Paint  |
| Туре               | A matt acrylic based paint containing texturing agents to provide a low slip risk potential surface in wet and dry conditions, available in red oxide and black colours.  |
| Intended Use       | For tiles, concrete and bricks. Not for use on glazed or quarry tiles.  |
| Special Features   | Quick drying and contains micronised red oxide pigment for good opacity. Dried surface finish rated as 'low slip risk potential' according to BS 7976, Part 2, 2002; Assessment of slip resistance in both wet and dry conditions.  |
| Preparation        | The surface must be clean, smooth, sound, dry and free from wax, dust and contaminants. Any wax polish previously applied can be removed with white spirit, steel wool and a clean rag. Existing paint, not being removed should be sanded to provide a key and cleaned with white spirit or detergent. |
| Application        | May form a soft crust on storage which must be stirred into the paint before use. Use a good quality brush and apply evenly.  |
| Coats              | 2 coats are usually sufficient. Sand lightly between coats if required.   |
| Drying Time        | 30 minutes depending on temperature and humidity. Do not apply outdoors if rain imminent.   |
| Re-coating Time    | Allow 4 hours between coats or overnight, depending on temperature and humidity.  |
| Application Temp.  | Ideally 15-25°C. Do not use below 10°C, or in conditions of high humidity or if rain imminent.  |
| Coverage           | 14 sq. metres per litre, per coat, depending on the absorbency of the surface.  |
| Maintenance        | Re-apply when surface becomes worn. The surface to be coated should be cleaned with a mild detergent solution or white spirit and lightly sanded to provide a key.  |
| Compatibility      | Can be applied over most paints but test for compatibility before applying.   |
| Settlement         | STIR WELL BEFORE USE.   |
| Shelf-life/Storage | Many years if stored in original, tightly closed container, in normal conditions.   |
| Hazards            | Keep out of reach of children. Avoid contact with skin and eyes. After contact with skin, wash immediately with plenty of soap and water. A full Safety Data Sheet is available upon request or on <a href="https://www.rustins.co.uk">www.rustins.co.uk</a>  |
| Clean-Up           | Remove excess product from brushes and then clean with water. Hard brushes can be cleaned with <b>Rustins Brush Restorer.</b>   |
| Sizes              | 500ml and 1 litre, (Black only available in 500ml).   |